

Issued: 06/01/2026

## EU DECLARATION OF CONFORMITY



Hereby, Flymaster Avionics Lda, declares under its sole responsibility that the following products are compliant with the essential requirements and other relevant provisions of the Radio Equipment directive (RED) 2014/53/EU and the restriction of the use of certain Hazardous Substances directive 2011/65/EU (EU RoHS 2) and its amendment directive (EU) 2015/863 (EU RoHS 3).

Product model: GPS LS2

Product name: Flymaster GPS LS2

Manufactured by: Flymaster Avionics, Lda.

Manufacturer's Address: Rua dos Fundões 151, 3700-121 São João da Madeira, Portugal

Type of Equipment: Sports navigation device

Directive 2014/53/EU (RED).

EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013 information technology equipment. Safety. General requirements:

EN 62368-1:2014

ETSI EN 301 489-1 V2.2.3 (2019-11)

ETSI EN 301 489-19 V2.1.1 (2019-4) Receive Only Mobile Earth stations.

ETSI EN 301 489-17 v3.1.1 (2017-02)

ETSI EN 301 489-3 v2.1.1 (2017-03)

ETSI EN 303 413 V1.1.1 (2017-6)

Directive 2015/863/EU (RoHS)

EN IEC 63000:2018

The undersigned does hereby declare that the equipment complies with the above directives and Standards.

Cristiano Pereira (Flymaster Avionics Partner)



06 January 2026, São João da Madeira, Portugal

## Documents



Warranty Terms



User Manual


# GPS LS<sup>2</sup>



## Read before use



### Register



Activation code

# Getting Started

## Hardware




## Power On



## Power Off



## Hard Reset



### 1. Description

A hard reset is a forced reboot of the GPS LS2 unit. It should be used when the device becomes unresponsive, freezes, or is unable to restart through normal operation. This procedure does not delete data or user settings.

### 2. When to Perform a Hard Reset

Perform a hard reset if:  
The device does not respond to any key presses.  
The screen is frozen or the system is locked.  
The unit cannot be powered off or restarted using standard methods.

### 3. Procedure

Identify the reset pinhole on the GPS LS2 housing.  
Insert a thin, rigid tool, such as a SIM card ejector tool or straightened paperclip into the pinhole.

Apply gentle pressure until the internal reset switch is activated. The device will shut down and automatically restart.

# Flight Pages

## Page 1



## Page 2



## Page 3

